



Front

Back



Description

The U3800-Coatings is a lightweight rooftop attachment solution consisting of an U-Anchor 3000 Series plate, flashing cover and separator membrane. The reinforcement is dependent on the type of coating being used, and therefore the method of installation may vary. *(Contact the technical team at Anchor Products for specific details)*

Advantages

- Lightweight: 5 oz. (142 grams).
- Installs quickly, approximately rate of 12 per man hour.
- Installs on any surface from flat to vertical.

U-Anchor Attachment

The U3800-Coatings is attached by fastening through the roofing assembly and into the structural decking with 2-4 approved fasteners, as directed by project specific engineering. Depending on the roofing manufacturer's requirements, the reinforcement type may vary, thereby changing the method of installation. Consult the coating manufacturer for proper application instructions.

Project-specific data is required to determine the correct type of fastener and number needed to secure each U-Anchor. An ANSI/SPRI FX-1 Pull Test is recommended to measure the pull-out resistance of fasteners included in the load path, (for example, substrate -> fasteners -> the U-Anchor -> other components.)

Equipment Attachment

To securely mount your rooftop equipment to the U-Anchor, after its installed, the connection nut must be tightened to approximately 20-25 ft.-lbs.

Use a calibrated torque wrench during install to ensure appropriate results are achieved.

Refer to product documentation for detailed installation and component requirements.

Testing

Results are based on plate performance only.

- Ultimate Load - Shear **X**: 9,597 lbs 
- Shear **Y**: 9,638 lbs 
- Ultimate Load - Tension: 4,997 lbs

Tested in accordance with ICC AC467

Individual roof deck assembly tests available upon request as application specific results may vary.

Warranty

- 20 Year Limited Material Only Warranty.
Subject to terms and conditions.

Product Specifications

Bolts

- 3/8"-16 x 1.5" Bolt*
- Material Type: 304 Stainless Steel

Plate

- Dimensions: 11.08" x 5.47"
- Fastener Hole Diameter: 0.265" (12 holes)
- Steel Thickness: 0.047" (1.194mm)
- Material Type: Galvanized Steel G90

Reinforcement Fabric

- Manufacturer: Non-Brand Specific*
- Color: Default White*
- Length: 17.5"
- Width: 11.75"
- Thickness: Default 60 mil*

Patents

- Visit www.anchorp.com/patents

Packaging Specifications

- Sold Individually OR Full Box Quantity
- Individual Weight: Approx. 1.4 lb
- Full Box Quantity: 10 units
- Box Weight: Approx. 18 lbs
- Box Dimensions: 19" x 14" x 14"
- Full Pallet Quantity: 24 boxes
- Pallet Dimensions: 48" x 40" x 62"

* Specified option is standard. Custom options may be available for additional charge. Lead times may apply depending on roofing manufacturer and product availability.

All representations herein are premised on proper installation and use of approved components. Failure to properly install or use of unapproved components voids all Anchor Products representations.

Anchor Products systems are included in many roofing manufacturers' guarantees! Please contact us for more information.

